



主轴静载  
**static load**  
2100 kg

最大载重  
**load**  
1000 kg

最大速度  
**speed**  
up to 1 m/s

曳引轮  
**sheave**  
100 mm

自重  
**weight**  
140 kg

额定扭矩 <b>Nominal Torque</b>	极数 <b>Poles</b>	编码器 <b>Encoder</b>	钢带轮 <b>Belt Pulley</b>		
			宽度 Width	钢带数 min - max	槽距 Pitch
<b>Nm</b>			mm	n°	mm
<b>164 S5 - 40% ED 180 s/h</b>	16	ERN1387 ECN1313 EI53C9.25 TS5213N2531	60	4	65
<b>制动器 Brake</b>					
EMFR DC110V/1.9A[2X200Nm]					

2:1	额定载重 Load	额定速度 Speed	曳引轮 Traction sheave				额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current 220V	额定电流 Current 380V				
			Ø	宽度 Width	n°	槽距 Pitch										
	kg	m/s	mm	mm		mm	Nm	kW	RPM	Hz	A	A				
800		0,4	100	60	4	65	127	2,03	153	20,4	9,3	5,9				
		0,5						2,54	191	25,5	14,7	7,4				
		1,0						5,08	382	50,9	19,3	9,3				
1000		0,4					100	60	4	65	159	2,54	153	20,4	11,6	6,8
		0,5										3,17	191	25,5	18,4	9,2
		1,0										6,35	382	50,9	24,3	11,6

- 1 - 以上数据是以平衡系数为45%的基础上计算出来的理论数据  
 1 - The values are obtained considering system balanced at the 45%  
 2 - 数据如有更改，恕不另行通知  
 2 - Data are subject to change without prior notice

