

| 代码<br>CODE | 导向轮直径<br>Pulley Diameter | 钢丝绳数量<br>N. of Ropes | 钢丝绳直径<br>Rope Diameter | 槽距<br>Pitch | 最大载重<br>Max Load |
|------------|--------------------------|----------------------|------------------------|-------------|------------------|
|            | mm                       | mm                   | mm                     | mm          | kg               |
| PS02000001 | 200                      | 5                    | 6                      | 10          | 900              |
| PS02000002 |                          | 6                    |                        |             |                  |
| PS02100003 | 210                      | 6                    | 6.5                    | 12          |                  |
| PS02300000 | 230                      | 5                    | 6                      | 10          |                  |
| PS02300001 |                          | 7                    |                        |             |                  |
| PS02400012 | 240                      | 5                    | 6                      | 10          |                  |
| PS02600000 | 260                      | 5                    | 6                      | 10          |                  |
| PS02600002 |                          | 6                    |                        |             |                  |
| PS02600003 |                          | 7                    |                        |             |                  |
| PS02600001 |                          | 8                    |                        |             |                  |
| PS03200020 | 320                      | 3                    | 8                      | 12          | 2100             |
| PS03200021 |                          | 4                    |                        |             |                  |
| PS03200022 |                          | 5                    |                        |             |                  |
| PS03200023 |                          | 6                    |                        |             |                  |
| PS03200024 |                          | 7                    |                        |             |                  |
| PS03200025 |                          | 8                    |                        | 17          | 2800             |
| PS03200026 |                          | 9                    |                        |             |                  |
| PS03200027 |                          | 3                    |                        |             |                  |
| PS03200028 |                          | 4                    |                        |             |                  |
| PS03200029 |                          | 5                    |                        |             |                  |
| PS03200030 | 6                        |                      |                        |             |                  |
| PS04000070 | 400                      | 3                    | 10                     | 14          | 2100             |
| PS04000071 |                          | 4                    |                        |             |                  |
| PS04000072 |                          | 5                    |                        |             |                  |
| PS04000073 |                          | 6                    |                        |             |                  |
| PS04000074 |                          | 7                    |                        |             |                  |
| PS04000075 |                          | 3                    |                        |             |                  |
| PS04000076 |                          | 4                    |                        |             |                  |
| PS04000077 |                          | 5                    |                        |             |                  |
| PS04000078 |                          | 6                    |                        |             |                  |

1 - 可以根据客户要求定制轴尺寸。

2 - 尼龙导向轮不能用于外部观光电梯。

3 - 对于尼龙导向轮，使用条件为曳引比2: 1，电梯厢侧导向轮为2个，对重侧导向轮为1个，速度低于2.0m/s。

1 - Customized shaft are available on request.

2 - Nylon pulleys can't be used for outdoor sightseeing lifts.

3 - For Nylon pulley, the common condition is Roping 2:1, Cabin pulley 2pcs, CTW pulley 1pcs, Speed less than 2.0m/s.

