



主轴静载
static load
8000 kg

最大载重
load
up to 2500 kg

最大速度
speed
up to 2,5 m/s

曳引轮
sheave
520 mm

自重
weight
1010 kg

额定扭矩 Nominal Torque	极数 Poles	编码器 Encoder	编码器线 Encoder Cable	绝缘等级 Insulation Class	可选项 Optional
2200 Nm S5 - 40% ED	32	Haidenhain1387	7m	F	Motor power cable 7m
制动器 Brake					
DZD1-21800 2X2172Nm-2x197W 2x1.8A-DC110V		DZD1-25000 2X3188Nm-2x(540/135)W 2x(2.7/1.35)A-DC200/100V		DZD1-21800 2X2715Nm-2x197W 2x1.8A-DC110V	

配件 - Accessories	
无机房 MRL	不适用 Not available for this model

1:1	电机Motor			曳引轮 Sheave				代码 CODE						
	额定载重 Load	额定速度 Speed	额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current		额定电压 Voltage	Ø	绳槽 Rope*	切口角 Angle*		槽距 Pitch
	kg	m/s	Nm	kW	RPM	Hz	A		V	mm	n°	β	γ	mm
MF800	1350	1.0	2097	8.1	37	9.79	19.6	380	520	7XØ13	95°	35°	20	MF800135015201340
		1.5		12.1	55	14.69	27.6							MF800135015201.5340
		1.75		14.1	64	17.14	32.5							MF800135015201.75340
		2.0		16.1	73	19.59	38.4							MF800135015202340

2:1	电机Motor			曳引轮 Sheave				代码 CODE						
	额定载重 Load	额定速度 Speed	额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current		额定电压 Voltage	Ø	绳槽 Rope*	切口角 Angle*		槽距 Pitch
	kg	m/s	Nm	kW	RPM	Hz	A		V	mm	n°	β	γ	mm
MF800	2000	1.0	1737	13.4	74	19.73	32.0	380	520	7xØ13	95°	35°	20	MF800200025201340
		1.5		20.0	110	29.38	44.0							MF800200025201.5340
		1.75		23.3	129	34.28	52.5							MF800200025201.75340
		2.0		26.7	147	39.18	62.5							MF800200025202340
		2.5		33.4	184	48.97	75.5							MF800200025202.5340
	2500	1.0	2172	16.7	74	19.73	35.0							MF800250025201340
		1.5		25.0	110	29.38	58.0							MF800250025201.5340
		1.75		29.2	129	34.28	66.0							MF800250025201.75340
		2.0		33.3	147	39.18	72.0							MF800250025202340
		2.5		41.8	184	48.97	94.0							MF800250025202.5340

1 - 数据如有更改，恕不另行通知
1 - Data are subject to change without prior notice

* 曳引轮绳槽数量和切口角可根据客户需求定制
Rope groove number, β and γ angles can be customized upon request

